



VMS4SE Multi-Channel Vibration Monitor

Alarm | Trip | Monitor
Communication | Logging



mVSCAN



The VMS4SE is an upgrade of model VMS4S; additional capabilities have been added by way of no. of channels, multi-serial ports, Ethernet port, scanning speed and alphanumeric display. VMS4SE accepts input directly from ICP type Accelerometer, processes the signal and gives analog output in the form of standard current or voltage to suit different applications in Power, Cement and Metal industries; Optionally VMS4SE also accepts Universal Analog input to serve various application.

Modular and Expandable

VMS4SE is modular in architecture and Expandable, I/O slots can accommodate a mix of Vibration Input, Analog Input, Open collector output or Relay output. All field inputs are wired by Pre-Fab cables direct into panel terminals.

Configuration

VMS4SE is used for plant wide predictive maintenance. It takes up online vibration and provides data through software. It is configured using the **mVSCAN** software which is very user friendly; the unit can also be edited by front keyboard and display. The unit has numeric and alphanumeric displays for value and tag display, Alarm/Trip and control status are displayed by discrete LEDs on front fascia.

Communication

VMS4SE comes with one RS-485 port as a standard, a second RS-485 port & an Ethernet Port are options to enhance the communication capabilities of the unit and for direct interface with PLC, DCS or SCADA

Buffer Output

VMS4SE comes with Field interface board with Buffered output on BNC connector for analysis purpose of raw signal of Vibration input.

Alarm/ Control

8 Relay and 16 OC outputs can be freely mapped as alarm/trip or control set point

Analog Output

An optional isolated 4-20mA analog output proportional to Vibration range is available to interface with PLC/DCS/RTU for centralized monitoring and protection. Max 8 output is possible.

Features

- 4 / 8 channel Vibration Input Module
- Optional 8 Channel Universal Analog Input Module
- 3 I/P & 2 O/P Slots capacity
- Compact and Rugged Panel Mount
- Extruded Aluminum Chassis with IP55 front fascia
- Field Configurable for Acceleration, Velocity or Displacement range
- Fast sampling and generation of Alarm/Trip
- User free mapping of Relay to Channels
- Comprehensive alarm/trip logic
- Alpha-Numeric display for programmable tag no / Engg unit
- RS485 Serial port (one standard and 2nd Optional)
- 1 x Ethernet port (Optional)
- Analog output (4-20 mA) [Optional]
- Field interface Buffer output Module
- Modbus RTU over serial and Modnet over Ethernet Protocols
- Windows based free **mVSCAN** configuration software
- Data logging option

Applications

- Balance of plant vibration measurement and protection of
 - Cooling towers
 - Pumps
 - Motors
 - Gear boxes
 - Blowers
 - ID/FD/PA Fans
 - Air compressors
 - Conveyors
- Motor/Generator/ Turbine Monitoring and Protection
- Compressor/Pump/DG set monitoring

USER-FRIENDLY PROGRAMMING AND ONLINE LOGGING

mVSCAN Software



mVSCAN Software is used to Monitor and Configure the Multichannel Vibration Monitor

- Auto device discovery of VMS4SE over RS485 Port
- Run Time Data monitoring
- Configuration through RS485 and Ethernet Port
- Data Log Retrieval(Periodic and Event) in .xls and .pdf file formats
- Online Data logging in .xlsx format
- Report Generation
- Alarm/Trip Setpoints
- Time Stamping

Easy to Monitor


Parameters	Front Display	mVSCAN software
Real-time data		
• Channel No.	✓	✓
• Process/Parameter Value	✓	✓
• Zero/Span, Input Type	✓	✓
• Alarm Status	✓	✓
• Channel wise Process/Parameter value	✓	✓

Programming using mVSCAN software



Online Logging using mVSCAN software

Application



AIR CENTRIFUGAL COMPRESSOR

PUMP/MOTOR

PUMP/MOTOR

TECHNICAL SPECIFICATIONS

Input		Buffered Output (Din Rail Mount Field Interface Module)		
Accelerometer Input		No of output per card	4 nos	
No of Modules	1 (4 ch), 2 (8ch)	Output Impedance	<100 ohms	
Type	Remote ICP piezoelectric Accelerometer	Frequency range	0.5Hz to 10KHz	
Sensitivity	100mV/g standard 500mV/g (on request)	Accuracy	0.25% of Full range	
Dynamic range	80 g pk	<p style="text-align: center;">Field Interface Module (BNC Port)</p>		
Measurement Parameters				
Parameter	Range (Field Selectable)			Resolution
Acceleration	0 to 50.0g (RMS, Pk)			0.1g
Velocity	0 to 100.0mm/sec (RMS, Pk)			0.1mm/sec
Displacement	0 to 2000microns (Pk-Pk)#			1 micron
Sensor Excitation current	4 mA approx.			*Derived Peak
Scan time	50 mSec/Channel			
Frequency range (factory set)	High Pass: 2.5Hz,5Hz,10Hz Low Pass: 1KHz,2.5KHz,10KHz -3dB Filter Accuracy : ± 10%			
Accuracy	± 2% of full span (Input to Display)			
Analog Input (Optional)		Data Logging (Optional)		
No of AI Modules	1 (8 ch)	Memory	25MB (Periodic), 7MB (Event)	
Input Type	Thermocouple, RTD, Voltage, Current	Logged data retrieval	VIA mVSCAN Software	
Input Range	Refer Table-1	Min Periodic Log Time	1 min	
Accuracy	0.1% FS	No of Records	101888 X $\left[\frac{256}{(2X\text{No. of Ch}) + 12} \right]$	
ADC Resolution	17 bits	Power supply		
Display Resolution	0.1 / 1.0 °C	Voltage	85-265VAC, 50/60 Hz / 100-295 VDC	
Sampling Rate	T/C & Voltage/Current: 50mSec/Channel RTD: 100mSec/Channel	Power Consumption	18 - 36VDC (Optional) 16VA (Max) [85-265V AC] 8VA (Max) [18-36VDC]	
Display Scan Rate	1 to 99 Sec (Programmable)	Isolation (Withstanding voltage)		
CJC	Auto/ Manual/ External for T/C type	Between primary terminals* and secondary terminals**: At least 1500 V AC for 1 minute Between primary terminals* and grounding terminal: At least 1500 V AC for 1 minute Between grounding terminal and secondary terminals**: At least 1500 V AC for 1 minute Between secondary terminals**: At least 500 V AC for 1 minute		
Sensor open	All inputs except 0-5V, 0-10VDC	* Primary terminals indicate power terminals and relay output terminals. **Secondary terminals indicate I/O signal and Communication O/P.		
Sensor Burnout current	0.4uA	Insulation resistance: 20MΩ or more @ 500 V DC between power terminals and grounding terminal		
RTD excitation current	250uA (Approx)	Physical		
NMRR	> 40dB	Size (in mm)	144 (H) X 72 (W) X 165 (D)	
CMRR	> 120dB	Panel Cutout (in mm)	137 (H) X 68.5 (W)	
Temp-co	< 100ppm/°C	Depth behind Panel (in mm)	155 / 203 (with cable connector)	
Input Impedance	> 1MΩ	Mounting	Panel Mount (Standard)	
Max Voltage	20VDC	Weight	1.25 Kg	
Connector type	24 pin Rectangular connector	Enclosure Material	Extruded Aluminum	
Display and Keys		Protection	IP20 (Overall), IP55 (Front Fascia)	
Channel number	2-Digit, 0.56", Green seven segment LED	Environmental		
Measuring Parameter Value	4-Digit, 0.56", Red seven segment LED	Operating temperature	-10 to 55 °C	
Engineering unit	6-Digit, 0.3", Orange Alphanumeric LED	Storage temperature	0 to 80 °C	
Status LEDs	Manual, Run, Flt, Tx/Rx, Relay status Alarm/Control Status per channel	Humidity	20 to 95 % RH non-condensing	
Keys	2 X 4 for Configuration, Operation and Calibration	Table 1: Display Range for Analog Input		
Output		Input Type		
Alarm/Trip Output (Optional)		Ranges		
Relay Output (Optional)		E	-200 °C to 1000 °C	
Relays	8 Nos per card	J	-200 °C to 1200 °C	
Type	C- NO or C-NC (Jumper Selectable)	K	-200 °C to 1372 °C	
Rating	2A @ 250VAC / 30VDC	T	-200 °C to 400 °C	
Connector type	25 D-Sub	B	400 °C to 1820 °C	
Open Collector (OC) Output (Optional)		R	0 °C to 1768 °C	
OC Outputs	16	S	0 °C to 1768 °C	
Type	Sinking	N	-200 °C to 1300 °C	
Rating	100mA@30VDC	Pt100	-199.0 °C to 850.0 °C	
Connector type	25 D-Sub	Cu53	-210.0 °C to 210.0 °C	
Analog Output (Optional)		NI-120	-70.0 °C to 210.0 °C	
No of Outputs	Max upto 8 nos per card	0/4 to 20mA (Ext.250Ω)	-1999 to 9999	
Output types	0/4 to 20 mA (Isolated)	0/1 to 5V		
Load	500Ω Max (for Current o/p) 3000Ω Min (for Voltage o/p)	-10 to 20 mV DC		
Accuracy	±0.1% of Full Scale (Display to output)	0 - 100 mV DC		
Communication Output		0 - 10 V DC		
RS485-1 (Standard) & RS485-2 (Optional)		Voltage/Current		
Protocol	Modbus-RTU Slave			
Baud Rate	9600 or 19200			
Connector	2 pin, plug-in terminals			
Ethernet (Optional)				
Protocol	Modbus - TCP/IP(Modnet) Slave			
Baud rate	10 Mbps			
Connector	RJ45			



TECHNICAL SPECIFICATIONS

Terminal Board for AI Module (Optional)

Input Connection	MKKDS type connector screw up to 2.5mm ² conductor
O/P Connection	25 Pin D-type plug in type Connector
Size (L X W X H) in mm	90 X 90 X 75
Mounting	35 mm DIN Rail

Terminal Board for Relay Module (Optional)

Input Connection	25 Pin D-type plug in type Connector
O/P Connection	MKDS type connector screw up to 2.5mm ² conductor
Size (L X W X H) in mm	90 X 90 X 75
Mounting	35 mm DIN Rail



Ordering Code

Model	Analog Output										Power Supply	Communication		Data logging		
	1	2		3		4		5								
VMS4SE	XX	XX	XX	XX	XX	XX	XX	XX	XX	XX	XX	XX	X			
	VI	4 channel Vib i/p	N	None	N	None	N	None	N	None	U1	85-265 VAC	1A	1 x RS485	N	No
	VI	4 channel Vib i/p	AI	8 ch Analog i/p	RL	8 Relay	4A	4 nos 4-20mA o/p	OC	Open Collector O/P	U2	18-36 VDC	2X	2 x RS485	Y	Yes
													1E	1 x RS485 + 1 x Ethernet		
													2E	2 x RS485 + 1 x Ethernet		

Note:

- Specify X from ordering code
- For Analog o/p type; other than 0/4-20mA please contact factory
- Customer to specify required input type/range from Table-1 for Analog input at the time of Order placement; else by default all analog channels will be calibrated for Input RTD PT100 range

Field Interface Board and Pre-fab cable for Vibration Input Ordering Code (Standard)

Part Code	Description
m-VMS4SE-FIB-VI	4 channel Field Interface Board for Vibration Input with BNC port for buffered output (4 Ch (VI): 1 Module Required & 8 ch (VI): 2 Modules Required)
VIC-2.5	4 points Input cable 25 Core 2.5 mtrs long 4 Ch (VI)

Prefab Cables Ordering Code (Optional)

Part Code	Description
AIC-2.5	8 points Input cable 25 Core 2.5 mtrs long 8 Ch (AI)
RLC-2.5	8 Relay output cable 25 Core 2.5 mtrs long
OCC-2.5	16 OC output cable, 25 Core 2.5 mtrs long
AOC-2.5	Analog output cable, 25 Core 2.5 mtrs long

Field Interface Terminal Board and Pre-fab cable for Analog Input Ordering Code (Extra Cost)

Part Code	Description
m-VMS4SE-FIB-AI	8 channel Field Interface Board for Analog Input (8 Ch (AI): 1 Module Required)
m-AIC-2.5-R24J-D25M	8 points Analog Input cable 25 Core 2.5 mtrs long with DB25 connector (8 Ch (AI): 1 Cable Required)

Field Interface Terminal Board and Pre-fab cable for Relay Output Ordering Code (Extra Cost)

Part Code	Description
m-VMS4SE-FIB-RL	8 channel Field Interface Board for Relay output
m-RLC-2.5-D25F-D25M	8 Relay output cable 25 Core 2.5 mtrs long with DB25 connector